https://cloudblue.com

Class AbstractHttpAdapter

This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at November 26, 2026

© Ingram Micro, Inc. All Rights Reserved.

Classes

AbstractHttpAdapter

> The *AbstractHttpAdapter* class allow a CloudBlue Connect SDK consumer to wrap a preferred http client library and adapt requests and responses to in order to work with this SDK.

DefaultHttpAdapter ⇐ `AbstractHttpAdapter`

> The *DefaultHttpAdapter* is the default adapter used in the CloudBlue Connect Javascript SDK based on the node-fetch http client library.

AbstractHttpAdapter

The *AbstractHttpAdapter* class allow a CloudBlue Connect SDK consumer to wrap a preferred http client library and adapt requests and responses to in order to work with this SDK.

Kind: global class
Category: Base

- AbstractHttpAdapter
  - new AbstractHttpAdapter(fetch)
  - .beforeRequest ⇒ `Array`

new AbstractHttpAdapter(fetch)

Create a subclass of AbstractHttpAdapter

Param	Type	Description
fetch	`function`	the fetch function used to make the actual http call.

abstractHttpAdapter.beforeRequest ⇒ `Array`

Get or set a list of beforeRequest hook functions.

© Ingram Micro, Inc. All Rights Reserved.

Kind: instance property of `AbstractHttpAdapter`
Returns: `Array` – Array of hooks.

DefaultHttpAdapter ⇐ `AbstractHttpAdapter`

The *DefaultHttpAdapter* is the default adapter used in the CloudBlue Connect Javascript SDK based on the node-fetch http client library.

Kind: global class
Extends: `AbstractHttpAdapter`
Category: Base

defaultHttpAdapter.beforeRequest ⇒ `Array`

Get or set a list of beforeRequest hook functions.

Kind: instance property of `DefaultHttpAdapter`
Overrides: `beforeRequest`
Returns: `Array` – Array of hooks.

© Ingram Micro, Inc. All Rights Reserved.