



<https://cloudblue.com>

[Documentation](#)  [Developer Resources](#)  [Connect SDK and Tools](#)  [Javascript SDK](#) 

# Class CategoryUsageFileResource



This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at July 4, 2026



## Classes

CategoryUsageFileResource  $\leftarrow$  GenericResource

The *CategoryUsageFileResource* class provides methods to access the *category* objects for a usage file.

UsageFileResource  $\leftarrow$  GenericResource

The *UsageFileResource* class provides methods to access the usage file endpoint of the Cloud Blue Connect API.

### **CategoryUsageFileResource** $\leftarrow$ GenericResource

The *CategoryUsageFileResource* class provides methods to access the *category* objects for a usage file.

**Kind:** global class

**Extends:** GenericResource

**Category:** Resources

### **UsageFileResource** $\leftarrow$ GenericResource

The *UsageFileResource* class provides methods to access the usage file endpoint of the Cloud Blue Connect API.

**Kind:** global class

**Extends:** GenericResource

**Category:** Resources

- UsageFileResource  $\leftarrow$  GenericResource
  - new UsageFileResource(client)
  - .categories(id)  $\Rightarrow$  CategoryUsageFileResource
  - .accept(id, acceptanceNote)  $\Rightarrow$  UsageFileResource
  - .approveAll(id)  $\Rightarrow$  UsageFileResource
  - .close(id)  $\Rightarrow$  UsageFileResource
  - .delete(id)  $\Rightarrow$  UsageFileResource
  - .reprocess(id)  $\Rightarrow$  UsageFileResource
  - .submit(id)  $\Rightarrow$  UsageFileResource
  - .reconciliation(id, reconFile)  $\Rightarrow$  UsageFileResource



- `.reject(id, rejectionNote) ⇒ UsageFileResource`
- `.upload(id, usageFile) ⇒ UsageFileResource`

### new UsageFileResource(client)

Creates a new instance of the *UsageFileResource* class.

**Returns:** `UsageFileResource` - An instance of the *UsageFileResource* class.

Param	Type	Description
client	<code>ConnectClient</code>	An instance of the <code>ConnectClient</code> class.

### usageFileResource.categories(id) ⇒ CategoryUsageFileResource

Returns an instance of the *CategoryUsageFileResource* for a *UsageFile*.

**Kind:** instance method of `UsageFileResource`

**Returns:** `CategoryUsageFileResource` - An instance of the *CategoryUsageFileResource* for the case.

Param	Type	Description
id	<code>string</code>	The unique identifier of the <i>UsageFile</i> .

### usageFileResource.accept(id, acceptanceNote) ⇒ UsageFileResource

Accept *Usage File*.

**Kind:** instance method of `UsageFileResource`

**Returns:** `UsageFileResource` - An instance of the *UsageFileResource*.

Param	Type	Description
id	<code>string</code>	The unique identifier of the <i>Usage File</i> .
acceptanceNote	<code>string</code>	Acceptance Note

### usageFileResource.approveAll(id) ⇒ UsageFileResource

Approve all *Usage File*.

**Kind:** instance method of `UsageFileResource`



**Returns:** UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

**usageFileResource.close(id) ⇒ UsageFileResource**

Close *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

**usageFileResource.delete(id) ⇒ UsageFileResource**

Delete *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

**usageFileResource.reprocess(id) ⇒ UsageFileResource**

Reprocess *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .



**usageFileResource.submit(id) ⇒ UsageFileResource**

Submit *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

**usageFileResource.reconciliation(id, reconFile) ⇒ UsageFileResource**

Reconciliation *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource - An instance of the *UsageFileResource*.

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .
reconFile	binary	Reconciliation binary file

**usageFileResource.reject(id, rejectionNote) ⇒ UsageFileResource**

Reject *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource - An instance of the *UsageFileResource*.

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .
rejectionNote	text	Rejection note

**usageFileResource.upload(id, usageFile) ⇒ UsageFileResource**

Upload *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource - An instance of the *UsageFileResource*.



<b>Param</b>	<b>Type</b>	<b>Description</b>
id	string	The unique identifier of the <i>Usage File</i> .
usageFile	binary	File to upload