



<https://cloudblue.com>

[Documentation](#) [Developer Resources](#) [Connect SDK and Tools](#) [Javascript SDK](#)

# Class CategoryUsageFileResource



This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at June 2, 2025



## Classes

CategoryUsageFileResource  $\Leftarrow$  GenericResource

The *CategoryUsageFileResource* class provides methods to access the *category* objects for a usage file.

UsageFileResource  $\Leftarrow$  GenericResource

The *UsageFileResource* class provides methods to access the usage file endpoint of the Cloud Blue Connect API.

### CategoryUsageFileResource $\Leftarrow$ GenericResource

The *CategoryUsageFileResource* class provides methods to access the *category* objects for a usage file.

**Kind:** global class

**Extends:** GenericResource

**Category:** Resources

### UsageFileResource $\Leftarrow$ GenericResource

The *UsageFileResource* class provides methods to access the usage file endpoint of the Cloud Blue Connect API.

**Kind:** global class

**Extends:** GenericResource

**Category:** Resources

- UsageFileResource  $\Leftarrow$  GenericResource
  - new UsageFileResource(client)
  - .categories(id)  $\Rightarrow$  CategoryUsageFileResource
  - .accept(id, acceptanceNote)  $\Rightarrow$  UsageFileResource
  - .approveAll(id)  $\Rightarrow$  UsageFileResource
  - .close(id)  $\Rightarrow$  UsageFileResource
  - .delete(id)  $\Rightarrow$  UsageFileResource
  - .reprocess(id)  $\Rightarrow$  UsageFileResource
  - .submit(id)  $\Rightarrow$  UsageFileResource
  - .reconciliation(id, reconFile)  $\Rightarrow$  UsageFileResource



- .reject(id, rejectionNote) ⇒ UsageFileResource
- .upload(id, usageFile) ⇒ UsageFileResource

**new UsageFileResource(client)**

Creates a new instance of the *UsageFileResource* class.

**Returns:** UsageFileResource - An instance of the *UsageFileResource* class.

Param	Type	Description
client	ConnectClient	An instance of the ConnectClient class.

**usageFileResource.categories(id) ⇒ CategoryUsageFileResource**

Returns an instance of the *CategoryUsageFileResource* for a *UsageFile*.

**Kind:** instance method of UsageFileResource  
**Returns:** CategoryUsageFileResource - An instance of the *CategoryUsageFileResource* for the case.

Param	Type	Description
id	string	The unique identifier of the <i>UsageFile</i> .

**usageFileResource.accept(id, acceptanceNote) ⇒ UsageFileResource**

Accept *Usage File*.

**Kind:** instance method of UsageFileResource  
**Returns:** UsageFileResource - An instance of the *UsageFileResource*.

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .
acceptanceNote	string	Acceptance Note

**usageFileResource.approveAll(id) ⇒ UsageFileResource**

Approve all *Usage File*.

**Kind:** instance method of UsageFileResource



**Returns:** UsageFileResource – An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

**usageFileResource.close(id) ⇒ UsageFileResource**

Close *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource – An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

**usageFileResource.delete(id) ⇒ UsageFileResource**

Delete *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource – An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

**usageFileResource.reprocess(id) ⇒ UsageFileResource**

Reprocess *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource – An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .



### usageFileResource.submit(id) ⇒ UsageFileResource

Submit *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource – An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

### usageFileResource.reconciliation(id, reconFile) ⇒ UsageFileResource

Reconciliation *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource – An instance of the *UsageFileResource*.

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .
reconFile	binary	Reconciliation binary file

### usageFileResource.reject(id, rejectionNote) ⇒ UsageFileResource

Reject *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource – An instance of the *UsageFileResource*.

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .
rejectionNote	text	Rejection note

### usageFileResource.upload(id, usageFile) ⇒ UsageFileResource

Upload *Usage File*.

**Kind:** instance method of UsageFileResource

**Returns:** UsageFileResource – An instance of the *UsageFileResource*.



Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .
usageFile	binary	File to upload