https://cloudblue.com

Class Directory

This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at November 13, 2026

© Ingram Micro, Inc. All Rights Reserved.

Directory

The Directory class exposes specialized methods to help
developers to access the directory (assets, tier configs, tier accounts).

Kind: global class
Category: Operations

- Directory
  - new Directory(client)
  - .searchAssets(query) ⇒ `Array`
  - .searchTierConfigurations(query) ⇒ `Array`
  - .searchTierAccounts(query) ⇒ `Array`
  - .getTierAccount(id) ⇒ `object`
  - .getAssetsByProductIdExternalId(productId, externalId) ⇒ `Array`
  - .createTierAccountRequest(request) ⇒ `object`
  - .searchTierAccountRequests(query) ⇒ `Array`
  - .getTierAccountRequest(id) ⇒ `object`
  - .acceptTierAccountRequest(id) ⇒ `object`
  - .ignoreTierAccountRequest(id, reason) ⇒ `object`
  - .getTierAccountVersion(id, version) ⇒ `object`

new Directory(client)

Creates an instance of the Directory class.

Returns: `Directory` – An instance of the Directory class.

Param	Type	Description
client	`ConnectClient`	An instance of the ConnectClient class.

directory.searchAssets(query) ⇒ `Array`

Returns a list of *Asset* objects that match the provided
(optional) query.

Kind: instance method of `Directory`
Returns: `Array` – An array of *Asset* object optionally matching the provided query.

© Ingram Micro, Inc. All Rights Reserved.

Param	Type	Description
query	`object`	The optional query to filter results.

directory.searchTierConfigurations(query) ⇒ `Array`

Returns a list of *TierConfiguration* objects that match the provided (optional) query.

Kind: instance method of `Directory`
Returns: `Array` – An array of *TierConfiguration* object optionally matching the provided query.

Param	Type	Description
query	`object`	The optional query to filter results.

directory.searchTierAccounts(query) ⇒ `Array`

Returns a list of *TierAccount* objects that match the provided (optional) query.

Kind: instance method of `Directory`
Returns: `Array` – An array of *TierAccount* object optionally matching the provided query.

Param	Type	Description
query	`object`	The optional query to filter results.

directory.getTierAccount(id) ⇒ `object`

Retrieve a *TierAccount* by its id.

Kind: instance method of `Directory`
Returns: `object` – The TierAccount object.

Param	Type	Description
id	`string`	The unique identifier of the TierAccount object.

© Ingram Micro, Inc. All Rights Reserved.

directory.getAssetsByProductIdExternalId(productId, externalId) ⇒ `Array`

Returns a list of *Asset* objects based on the productId and the *Asset* externalId.

Kind: instance method of `Directory`
Returns: `Array` – An array of *Asset* objects.

Param	Type	Description
productId	`string`	The unique id of the *Product* related to this *Asset*.
externalId	`string`	The external identifier of the *Asset*.

directory.createTierAccountRequest(request) ⇒ `object`

Creates a new *TierAccountRequest*

Kind: instance method of `Directory`
Returns: `object` – The created TierAccountRequest object.

Param	Type	Description
request	`object`	The TierAccountRequest object.

directory.searchTierAccountRequests(query) ⇒ `Array`

Returns a list of *TierAccountRequest* objects that match the provided filters.

Kind: instance method of `Directory`
Returns: `Array` – An array of *TierAccountRequest* objects that match the provided filters.

Param	Type	Description
query	`object`	A RQL query.

directory.getTierAccountRequest(id) ⇒ `object`

Retrieve the *TierAccountRequest* object identified by its id.

© Ingram Micro, Inc. All Rights Reserved.

Kind: instance method of `Directory`
Returns: `object` – The *TierAccountRequest* object.

Param	Type	Description
id	`string`	The unique identifier of the *TierAccountRequest* object.

directory.acceptTierAccountRequest(id) ⇒ `object`

Accept the *TierAccountRequest* object identified by its id.

Kind: instance method of `Directory`
Returns: `object` – The *TierAccountRequest* object.

Param	Type	Description
id	`string`	The unique identifier of the *TierAccountRequest* object.

directory.ignoreTierAccountRequest(id, reason) ⇒ `object`

Ignore the *TierAccountRequest* object identified by its id.

Kind: instance method of `Directory`
Returns: `object` – The *TierAccountRequest* object.

Param	Type	Description
id	`string`	The unique identifier of the *TierAccountRequest* object.
reason	`string`	The reason for which this request has been ignored.

directory.getTierAccountVersion(id, version) ⇒ `object`

Returns the specified version of the *TierAccount* object identified by its id.

Kind: instance method of `Directory`
Returns: `object` – The *TierAccount* object.

Param	Type	Description
id	`string`	The unique identifier of the *TierAccount* object.
version	`string`	The version to be retrieved.

© Ingram Micro, Inc. All Rights Reserved.