



<https://cloudblue.com>

[Documentation](#)  [Developer Resources](#)  [Connect SDK and Tools](#)  [Javascript SDK](#) 

Class `HttpError`



This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at July 2, 2026



Classes

HttpError \leftarrow Error

HttpError wraps any http response which status is \neq 2xx.

APIError \leftarrow HttpError

APIError wraps CloudBlue Connect API errors.
 Provides convenient methods to obtains error code and error messages.
 The Cloud Blue Connect JSON error looks like:

HttpError \leftarrow Error

HttpError wraps any http response which status is \neq 2xx.

Kind: global class

Extends: Error

Category: Base

- HttpError \leftarrow Error
 - new HttpError(status, message)
 - .status : number

new HttpError(status, message)

Create a new instance of the HttpError class.

| Param | Type | Description |
|---------|--------|-----------------------|
| status | number | the http status code. |
| message | string | an error message. |

httpError.status : number

The http status code.

Kind: instance property of HttpError



APIError ← HttpError

APIError wraps CloudBlue Connect API errors. Provides convenient methods to obtains error code and error messages.

The Cloud Blue Connect JSON error looks like:

Kind: global class

Extends: HttpError

Category: Base

- APIError ← HttpError
 - new APIError(status, message)
 - .json ⇒ object
 - .errorCode ⇒ string
 - .errors ⇒ Array
 - .status : number

new APIError(status, message)

Create a new instance of the APIError class.

| Param | Type | Description |
|---------|--------|--------------------------|
| status | number | the http status code. |
| message | string | A JSON parseable object. |

Example

```
{
  "error_code": "SYS_001",
  "errors": [
    "error message 1"
  ]
}
```

apiError.json ⇒ object

Returns the JSON error object.

Kind: instance property of APIError

Returns: object - The error object.



apiError.errorCode ⇒ string

Returns the error code.

Kind: instance property of APIError

Returns: string - The error code.

apiError.errors ⇒ Array

Returns an array of error messages.

Kind: instance property of APIError

Returns: Array - The error messages.

apiError.status : number

The http status code.

Kind: instance property of APIError

Overrides: status