Class HttpError

This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at April 19, 2024

© Ingram Micro, Inc. All Rights Reserved.

Classes

HttpError ⇐ `Error`

HttpError wraps any http response which status is != 2xx.

APIError ⇐ `HttpError`

APIError wraps CloudBlue Connect API errors.
Provides convenient methods to obtains error
code and error messages.
The Cloud Blue Connect JSON error looks like:

HttpError ⇐ `Error`

HttpError wraps any http response which status is != 2xx.

Kind: global class
Extends: `Error`
Category: Base

- HttpError ⇐ `Error`
  - new HttpError(status, message)
  - .status : `number`

new HttpError(status, message)

Create a new instance of the HttpError class.

Param	Type	Description
status	`number`	the http status code.
message	`string`	an error message.

httpError.status : `number`

The http status code.

Kind: instance property of `HttpError`

© Ingram Micro, Inc. All Rights Reserved.

APIError ⇐ `HttpError`

APIError wraps CloudBlue Connect API errors.
Provides convenient methods to obtains error
code and error messages.
The Cloud Blue Connect JSON error looks like:

Kind: global class
Extends: `HttpError`
Category: Base

- APIError ⇐ `HttpError`
  - new APIError(status, message)
  - .json ⇒ `object`
  - .errorCode ⇒ `string`
  - .errors ⇒ `Array`
  - .status : `number`

new APIError(status, message)

Create a new instance of the APIError class.

Param	Type	Description
status	`number`	the http status code.
message	`string`	A JSON parseable object.

Example

```
{
   "error_code": "SYS_001",
   "errors": [
      "error message 1"
   ]
}
```

apiError.json ⇒ `object`

Returns the JSON error object.

Kind: instance property of `APIError`
Returns: `object` – The error object.

© Ingram Micro, Inc. All Rights Reserved.

apiError.errorCode ⇒ `string`

Returns the error code.

Kind: instance property of `APIError`
Returns: `string` – The error code.

apiError.errors ⇒ `Array`

Returns an array of error messages.

Kind: instance property of `APIError`
Returns: `Array` – The error messages.

apiError.status : `number`

The http status code.

Kind: instance property of `APIError`
Overrides: `status`

© Ingram Micro, Inc. All Rights Reserved.