

[Documentation](#) → [Developer Resources](#) → [Connect SDK and Tools](#) → [Javascript SDK](#) →

Class RequestResource



This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at July 16, 2024

RequestResource \leftarrow GenericResource

The *RequestResource* class provides methods to access the *Request* endpoint of the Cloud Blue Connect API.

Kind: global class

Extends: GenericResource

Category: Resources

- RequestResource \leftarrow GenericResource
 - new RequestResource(client)
 - .fail(id, reason) \Rightarrow object
 - .inquire(id, request) \Rightarrow object
 - .approve(id, request) \Rightarrow object
 - .pending(id) \Rightarrow object

new RequestResource(client)

Creates a new instance of the *RequestResource* class.

Returns: RequestResource - An instance of the *RequestResource* class.

Param	Type	Description
client	ConnectClient	An instance of the ConnectClient class.

requestResource.fail(id, reason) \Rightarrow object

Change the status of a *Request* to fail.

Kind: instance method of RequestResource

Returns: object - The updated Request object.

Param	Type	Description
id	string	The unique identifier of the Request object.
reason	string	The reason for which the Request has been failed.

requestResource.inquire(id, request) \Rightarrow object

Change the status of a *Request* to inquire.

To change the status of the Request to inquire you must provide either a template id or a template tile.

Kind: instance method of RequestResource

Returns: object - The updated Request object.

Param	Type	Description
id	string	The unique identifier of the Request object.
request	object	The request body.

Example

```
// request body using a template id
{
  template_id: 'TL-827-840-476'
}
```

Example

```
// request body using an activation tile
{
  activation_tile: '<rendered text>'
}
```

requestResource.approve(id, request) ⇒ object

Change the status of a *Request* to approved.

To change the status of the Request to approved you must provide either a template id or a template tile.

Kind: instance method of RequestResource

Returns: object - The updated Request object.

Param	Type	Description
id	string	The unique identifier of the Request object.
request	object	The request body.

Example

```
// request body using a template id
{
```

```
template_id: 'TL-827-840-476'
}
```

Example

```
// request body using an activation tile
{
  activation_tile: '<rendered text>'
}
```

requestResource.pending(id) ⇒ object

Change the status of a *Request* to pending.

Kind: instance method of RequestResource

Returns: object - The updated Request object.

Param	Type	Description
id	string	The unique identifier of the Request object.