https://cloudblue.com

Class RequestResource

This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at November 26, 2026

© Ingram Micro, Inc. All Rights Reserved.

RequestResource ⇐ `GenericResource`

The *RequestResource* class provides methods to access the *Request* endpoint of the Cloud Blue Connect API.

Kind: global class
Extends: `GenericResource`
Category: Resources

- RequestResource ⇐ `GenericResource`
  - new RequestResource(client)
  - .fail(id, reason) ⇒ `object`
  - .inquire(id, request) ⇒ `object`
  - .approve(id, request) ⇒ `object`
  - .pending(id) ⇒ `object`

new RequestResource(client)

Creates a new instance of the *RequestResource* class.

Returns: `RequestResource` – An instance of the *RequestResource* class.

Param	Type	Description
client	`ConnectClient`	An instance of the ConnectClient class.

requestResource.fail(id, reason) ⇒ `object`

Change the status of a *Request* to fail.

Kind: instance method of `RequestResource`
Returns: `object` – The updated Request object.

Param	Type	Description
id	`string`	The unique identifier of the Request object.
reason	`string`	The reason for which the Request has been failed.

requestResource.inquire(id, request) ⇒ `object`

Change the status of a *Request* to inquire.

© Ingram Micro, Inc. All Rights Reserved.

To change the status of the Request to inquire you must provide
either a template id or a template tile.

Kind: instance method of `RequestResource`
Returns: `object` – The updated Request object.

Param	Type	Description
id	`string`	The unique identifier of the Request object.
request	`object`	The request body.

Example

```
// request body using a template id
{
  template_id: 'TL-827-840-476'
}
```

Example

```
// request body using an activation tile
{
  activation_tile: '<rendered text>'
}
```

requestResource.approve(id, request) ⇒ `object`

Change the status of a *Request* to approved.
To change the status of the Request to approved you must provide
either a template id or a template tile.

Kind: instance method of `RequestResource`
Returns: `object` – The updated Request object.

Param	Type	Description
id	`string`	The unique identifier of the Request object.
request	`object`	The request body.

Example

```
// request body using a template id
{
```


© Ingram Micro, Inc. All Rights Reserved.

```
  template_id: 'TL-827-840-476'
}
```

Example

```
// request body using an activation tile
{
  activation_tile: '<rendered text>'
}
```

requestResource.pending(id) ⇒ `object`

Change the status of a *Request* to pending.

Kind: instance method of `RequestResource`
Returns: `object` – The updated Request object.

Param	Type	Description
id	`string`	The unique identifier of the Request object.

© Ingram Micro, Inc. All Rights Reserved.