https://cloudblue.com

Class TierConfigRequestResource

This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at November 12, 2026

© Ingram Micro, Inc. All Rights Reserved.

TierConfigRequestResource ⇐ `GenericResource`

The *TierConfigRequestResource* class provides methods to access the *TierConfigRequest* endpoint of the Cloud Blue Connect API.

Kind: global class
Extends: `GenericResource`
Category: Resources

- TierConfigRequestResource ⇐ `GenericResource`
  - new TierConfigRequestResource(client)
  - .fail(id, reason)
  - .inquire(id)
  - .pending(id)
  - .approve(id, request) ⇒ `object`

new TierConfigRequestResource(client)

Creates a new instance of the *TierConfigRequestResource* class.

Returns: `TierConfigRequestResource` – An instance of the *TierConfigRequestResource* class.

Param	Type	Description
client	`ConnectClient`	An instance of the ConnectClient class.

tierConfigRequestResource.fail(id, reason)

Changes the status of a *TierConfigurationRequest* to fail.

Kind: instance method of `TierConfigRequestResource`

Param	Type	Description
id	`string`	The unique identifier of the TierConfigurationRequest object.
reason	`string`	The reason for which the TierConfigurationRequest has been failed.

tierConfigRequestResource.inquire(id)

Changes the status of a *TierConfigurationRequest* to inquire.
Kind: instance method of `TierConfigRequestResource`

© Ingram Micro, Inc. All Rights Reserved.

Param	Type	Description
id	`string`	The unique identifier of the TierConfigurationRequest object.

tierConfigRequestResource.pending(id)

Changes the status of a *TierConfigurationRequest* to pending.

Kind: instance method of `TierConfigRequestResource`

Param	Type	Description
id	`string`	The unique identifier of the TierConfigurationRequest object.

tierConfigRequestResource.approve(id, request) ⇒ `object`

Change the status of a *TierConfigurationRequest* to approved.
To change the status of the TierConfigurationRequest to approved
you must provide a Template id.

Kind: instance method of `TierConfigRequestResource`
Returns: `object` – The rendered Template.

Param	Type	Description
id	`string`	The unique identifier of the TierConfigurationRequest object.
request	`object`	The request body.

Example

```
// request body using a template id
{
  template: {
    id: 'TL-000-000-000'
  }
}
```


© Ingram Micro, Inc. All Rights Reserved.