

[Documentation](#) → [Developer Resources](#) → [Connect SDK and Tools](#) → [Javascript SDK](#) →

Class TierConfigRequestResource



This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at July 16, 2024

TierConfigRequestResource \Leftarrow GenericResource

The *TierConfigRequestResource* class provides methods to access the *TierConfigRequest* endpoint of the Cloud Blue Connect API.

Kind: global class

Extends: GenericResource

Category: Resources

- TierConfigRequestResource \Leftarrow GenericResource
 - new TierConfigRequestResource(client)
 - .fail(id, reason)
 - .inquire(id)
 - .pending(id)
 - .approve(id, request) \Rightarrow object

new TierConfigRequestResource(client)

Creates a new instance of the *TierConfigRequestResource* class.

Returns: TierConfigRequestResource - An instance of the *TierConfigRequestResource* class.

Param	Type	Description
client	ConnectClient	An instance of the ConnectClient class.

tierConfigRequestResource.fail(id, reason)

Changes the status of a *TierConfigurationRequest* to fail.

Kind: instance method of TierConfigRequestResource

Param	Type	Description
id	string	The unique identifier of the TierConfigurationRequest object.
reason	string	The reason for which the TierConfigurationRequest has been failed.

tierConfigRequestResource.inquire(id)

Changes the status of a *TierConfigurationRequest* to inquire.

Kind: instance method of TierConfigRequestResource

Param	Type	Description
id	string	The unique identifier of the TierConfigurationRequest object.

tierConfigRequestResource.pending(id)

Changes the status of a *TierConfigurationRequest* to pending.

Kind: instance method of TierConfigRequestResource

Param	Type	Description
id	string	The unique identifier of the TierConfigurationRequest object.

tierConfigRequestResource.approve(id, request) ⇒ object

Change the status of a *TierConfigurationRequest* to approved.

To change the status of the TierConfigurationRequest to approved you must provide a Template id.

Kind: instance method of TierConfigRequestResource

Returns: object - The rendered Template.

Param	Type	Description
id	string	The unique identifier of the TierConfigurationRequest object.
request	object	The request body.

Example

```
// request body using a template id
{
  template: {
    id: 'TL-000-000-000'
  }
}
```