

[Documentation](#) → [Developer Resources](#) → [Connect SDK and Tools](#) → [Javascript SDK](#) →

Class UsageFileResource



This article has been generated from the online version of the documentation and might be out of date. Please, make sure to always refer to the online version of the documentation for the up-to-date information.

Auto-generated at June 28, 2022

Classes

CategoryUsageFileResource \leftarrow GenericResource

The *CategoryUsageFileResource* class provides methods to access the *category* objects for a usage file.

UsageFileResource \leftarrow GenericResource

The *UsageFileResource* class provides methods to access the usage file endpoint of the Cloud Blue Connect API.

CategoryUsageFileResource \leftarrow GenericResource

The *CategoryUsageFileResource* class provides methods to access the *category* objects for a usage file.

Kind: global class

Extends: GenericResource

Category: Resources

UsageFileResource \leftarrow GenericResource

The *UsageFileResource* class provides methods to access the usage file endpoint of the Cloud Blue Connect API.

Kind: global class

Extends: GenericResource

Category: Resources

- UsageFileResource \leftarrow GenericResource
 - new UsageFileResource(client)
 - .categories(id) \Rightarrow CategoryUsageFileResource
 - .accept(id, acceptanceNote) \Rightarrow UsageFileResource
 - .approveAll(id) \Rightarrow UsageFileResource
 - .close(id) \Rightarrow UsageFileResource
 - .delete(id) \Rightarrow UsageFileResource
 - .reprocess(id) \Rightarrow UsageFileResource
 - .submit(id) \Rightarrow UsageFileResource
 - .reconciliation(id, reconFile) \Rightarrow UsageFileResource

- `.reject(id, rejectionNote) ⇒ UsageFileResource`
- `.upload(id, usageFile) ⇒ UsageFileResource`

new UsageFileResource(client)

Creates a new instance of the *UsageFileResource* class.

Returns: `UsageFileResource` - An instance of the *UsageFileResource* class.

Param	Type	Description
client	<code>ConnectClient</code>	An instance of the <code>ConnectClient</code> class.

usageFileResource.categories(id) ⇒ CategoryUsageFileResource

Returns an instance of the *CategoryUsageFileResource* for a *UsageFile*.

Kind: instance method of `UsageFileResource`

Returns: `CategoryUsageFileResource` - An instance of the *CategoryUsageFileResource* for the case.

Param	Type	Description
id	<code>string</code>	The unique identifier of the <i>UsageFile</i> .

usageFileResource.accept(id, acceptanceNote) ⇒ UsageFileResource

Accept *Usage File*.

Kind: instance method of `UsageFileResource`

Returns: `UsageFileResource` - An instance of the *UsageFileResource*.

Param	Type	Description
id	<code>string</code>	The unique identifier of the <i>Usage File</i> .
acceptanceNote	<code>string</code>	Acceptance Note

usageFileResource.approveAll(id) ⇒ UsageFileResource

Approve all *Usage File*.

Kind: instance method of `UsageFileResource`

Returns: UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

usageFileResource.close(id) ⇒ UsageFileResource

Close *Usage File*.

Kind: instance method of UsageFileResource

Returns: UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

usageFileResource.delete(id) ⇒ UsageFileResource

Delete *Usage File*.

Kind: instance method of UsageFileResource

Returns: UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

usageFileResource.reprocess(id) ⇒ UsageFileResource

Reprocess *Usage File*.

Kind: instance method of UsageFileResource

Returns: UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

usageFileResource.submit(id) ⇒ UsageFileResource

Submit *Usage File*.

Kind: instance method of UsageFileResource

Returns: UsageFileResource - An instance of the *UsageFileResource*

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .

usageFileResource.reconciliation(id, reconFile) ⇒ UsageFileResource

Reconciliation *Usage File*.

Kind: instance method of UsageFileResource

Returns: UsageFileResource - An instance of the *UsageFileResource*.

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .
reconFile	binary	Reconciliation binary file

usageFileResource.reject(id, rejectionNote) ⇒ UsageFileResource

Reject *Usage File*.

Kind: instance method of UsageFileResource

Returns: UsageFileResource - An instance of the *UsageFileResource*.

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .
rejectionNote	text	Rejection note

usageFileResource.upload(id, usageFile) ⇒ UsageFileResource

Upload *Usage File*.

Kind: instance method of UsageFileResource

Returns: UsageFileResource - An instance of the *UsageFileResource*.

Param	Type	Description
id	string	The unique identifier of the <i>Usage File</i> .
usageFile	binary	File to upload